



GS3 PREMIUM GERMAN ADAPTOR

ELECTRICAL

Rated Voltage	250V a.c.
Rated Current	16Amp
Frequency	50Hz / 60Hz
Led	Power Dissipation : 100mWatt , Foward Current : 25mAmp

ENVIRONMENTAL

Ambient Operating Temperature	-5°C to +40°C (not to exceed an average of more than 25°C in any 24 hours period)
Degree of Protection	Ordinary

MATERIAL

Material (Enclosure)	Polycarbonate
Metal Components Material	Brass, Phosphors Bronze

SIZE AND WEIGHT

Dimension (Diameter x Depth)	67mm x 58mm
Weight	Estimated 82 grams

Led	Power Dissipation : 100mW , Foward Current : 25mA
Guarantee	1 year subject to Eubiq Limited Warranty Statement



www.eubiq.com

EUBIQ PRIVATE LIMITED. 9 JOO KOON CRESCENT SINGAPORE 629025
ALL RIGHTS RESERVED. EUBIQ AND GSS ARE REGISTERED TRADEMARKS OF EUBIQ PTE LTD.

DISCLAIMER: EUBIQ PRIVATE LIMITED RESERVES THE RIGHT TO ALTER ANY DETAILS OF SPECIFICATIONS OR EQUIPMENT WITHOUT PRIOR NOTICE. DETAILS OF SPECIFICATIONS AND EQUIPMENT ARE ALSO SUBJECT TO CHANGES TO SUIT LOCAL STANDARDS, CONDITIONS AND REQUIREMENTS. PLEASE CONSULT YOUR LOCAL DEALER FOR MORE INFORMATION OR LOGON TO EUBIQ WEBSITE.