



Front View


DMS1 POWER AND CABLE MANAGEMENT TRACK

Track Used

SFC3 Modular Track

ELECTRICAL

Compartment Capacity



Housing Capacity

	Empty Compartment	With SFC2 Track	With DS4 Data Socket Housing
A	2569 mm ²	1227 mm ²	2166 mm ²
B	2487 mm ²	1145 mm ²	2084 mm ²

* Above capacity area value are estimated and rounded up to nearest figure.

Cable Size Guide

	Type of Cable	Size
Data Cables	Cat. 5E UTP	Dia 5.5mm *
	Cat. 5E STP	Dia 6.0mm *
	Cat. 6 UTP	Dia 6.5mm *
	Cat. 6 STP	Dia 7.0mm *

* Typical Values, please check with manufacturer.

** It is recommended that each compartment is not filled over 45% of its full capacity.

MATERIAL

Track

Aluminium

Insulation

Polycarbonate

SIZE AND WEIGHT (Based on 1 meter Length)

Dimension (Width x Depth)

150mm x 40mm

Weight

Estimated 3.6 kilograms
(1m of SFC3 Modular Track with 1m of DMS1 Housing)

Accessories

SFC3 Modular Track

SFC2 Blank Cover

SFC2 Housing Joint Pin

DS4 Data Socket Housing Assembly

DMS1 Internal Corner Cap

DMS1 External Corner Cap

DMS1 Corner Link

Guarantee

3 years subject to Eubiq Limited Warranty Statement
(Applicable to track ONLY)



www.eubiq.com

EUBIQ PRIVATE LIMITED. 9 JOO KOON CRESCENT SINGAPORE 629025
ALL RIGHTS RESERVED. EUBIQ AND GSS ARE REGISTERED TRADEMARKS OF EUBIQ PTE LTD.

DISCLAIMER: EUBIQ PRIVATE LIMITED RESERVES THE RIGHT TO ALTER ANY DETAILS OF SPECIFICATIONS OR EQUIPMENT WITHOUT PRIOR NOTICE. DETAILS OF SPECIFICATIONS AND EQUIPMENT ARE ALSO SUBJECT TO CHANGES TO SUIT LOCAL STANDARDS, CONDITIONS AND REQUIREMENTS. PLEASE CONSULT YOUR LOCAL DEALER FOR MORE INFORMATION OR LOGON TO EUBIQ WEBSITE.



Front View

SFC3 MODULAR TRACK

ELECTRICAL

Rated Voltage	250V a.c. Single-phase
Rated Current	32 Amp maximum
Frequency	50Hz / 60Hz
Rated Impulse Withstand Voltage	4000V a.c.
Connection of Adaptor or Tap-off Unit	Intended to be connected and disconnected when system is energized and with a load connected
Terminal Capacity: Live, Neutral & Earth	1.25 mm ² to 6 mm ²

ENVIRONMENTAL

Ambient Operating Temperature	-5°C to +55°C (not to exceed an average of more than 35°C in any 24 hours period)
Maximum Installation Altitude	2000 meters
Resistance to Impact	Heavy Impact
Degree of Protection	IP4X
Degree of Pollution	2 (Non-conductive pollution with temporary conductivity caused by condensation)

MATERIAL

Track	Aluminium
Insulation	Polycarbonate

SIZE AND WEIGHT (Based On 1 meter Length)

Overall Dimension (Width x Depth)	62mm x 26mm
Weight	Estimated 1.2 kilograms
Compliance	IEC EN 61534-1, IEC EN 61534-21 (DEKRA/KEMA tested) DNV Standard for Certification No 2.4 (PSB Tested)
Guarantee	3 years subject to Eubiq Limited Warranty Statement (Applicable to track ONLY)