




## SC2 ULTRA COMPACT TRACK

Track Used	SFC3 Modular Track
ELECTRICAL	

### Compartment Capacity



### Housing Capacity

	Empty Compartment	With SFC3 Track
A	1768mm <sup>2</sup>	86mm <sup>2</sup>


MATERIAL	
Track	Aluminium
Insulation	Polycarbonate
SIZE AND WEIGHT (Based on 1 meter Length)	
Dimension (Width x Depth)	70mm x 28mm
Weight	Estimated 0.7 kilograms (Housing only)
Accessories	SFC3 Modular Track SFC2 Blank Cover SC2 End Cap
Guarantee	3 years subject to Eubiq Limited Warranty Statement (Applicable to track ONLY)



[www.eubiq.com](http://www.eubiq.com)

EUBIQ PRIVATE LIMITED. 9 JOO KOON CRESCENT SINGAPORE 629025  
ALL RIGHTS RESERVED. EUBIQ AND GSS ARE REGISTERED TRADEMARKS OF EUBIQ PTE LTD.

DISCLAIMER: EUBIQ PRIVATE LIMITED RESERVES THE RIGHT TO ALTER ANY DETAILS OF SPECIFICATIONS OR EQUIPMENT WITHOUT PRIOR NOTICE. DETAILS OF SPECIFICATIONS AND EQUIPMENT ARE ALSO SUBJECT TO CHANGES TO SUIT LOCAL STANDARDS, CONDITIONS AND REQUIREMENTS. PLEASE CONSULT YOUR LOCAL DEALER FOR MORE INFORMATION OR LOGON TO EUBIQ WEBSITE.



Front View

## SFC3 MODULAR TRACK

### ELECTRICAL

Rated Voltage	250V a.c. Single-phase
Rated Current	32 Amp maximum
Frequency	50Hz / 60Hz
Rated Impulse Withstand Voltage	4000V a.c.
Connection of Adaptor or Tap-off Unit	Intended to be connected and disconnected when system is energized and with a load connected
Terminal Capacity: Live, Neutral & Earth	1.25 mm <sup>2</sup> to 6 mm <sup>2</sup>

### ENVIRONMENTAL

Ambient Operating Temperature	-5°C to +55°C (not to exceed an average of more than 35°C in any 24 hours period)
Maximum Installation Altitude	2000 meters
Resistance to Impact	Heavy Impact
Degree of Protection	IP4X
Degree of Pollution	2 (Non-conductive pollution with temporary conductivity caused by condensation)

### MATERIAL

Track	Aluminium
Insulation	Polycarbonate

### SIZE AND WEIGHT (Based On 1 meter Length)

Overall Dimension (Width x Depth)	62mm x 26mm
Weight	Estimated 1.2 kilograms
Compliance	IEC EN 61534-1, IEC EN 61534-21 (DEKRA/KEMA tested) DNV Standard for Certification No 2.4 (PSB Tested)
Guarantee	3 years subject to Eubiq Limited Warranty Statement (Applicable to track ONLY)