



## SWT PREMIUM WALL TERMINAL

### ELECTRICAL

Rated Voltage	250V a.c.
Rated Current	10 Amp / 13 Amp / 16Amp
Frequency	50Hz / 60Hz
Terminal Capacity: Live, Neutral & Earth	22.5 mm <sup>2</sup>

### ENVIRONMENTAL

Ambient Operating Temperature	-5°C to +40°C (not to exceed an average of more than 35°C in any 24 hours period)
Degree of Protection	IP20

### MATERIAL

Material (Enclosure)	Polycarbonate, Glass
Metal Component Material	Brass, Phosphors Bronze

### SIZE AND WEIGHT

Dimension (Height x Width x Depth)	86mm x 86mm x 28mm
Weight	Estimated 95 grams
Fixing Center	60mm

Recommended Flush Boxes	'ABB', 'Jung' Moulded Type and Steel Type Depth: min. 35mm Flush Boxes shall be complied to BS 4662
Guarantee	1 year subject to Eubiq Limited Warranty Statement



[www.eubiq.com](http://www.eubiq.com)

EUBIQ PRIVATE LIMITED, 9 JOO KOON CRESCENT SINGAPORE 629025  
ALL RIGHTS RESERVED. EUBIQ AND GSS ARE REGISTERED TRADEMARKS OF EUBIQ PTE LTD.

DISCLAIMER: EUBIQ PRIVATE LIMITED RESERVES THE RIGHT TO ALTER ANY DETAILS OF SPECIFICATIONS OR EQUIPMENT WITHOUT PRIOR NOTICE. DETAILS OF SPECIFICATIONS AND EQUIPMENT ARE ALSO SUBJECTED TO CHANGES TO SUIT LOCAL STANDARDS, CONDITIONS AND REQUIREMENTS. PLEASE CONSULT YOUR LOCAL DEALER FOR MORE INFORMATION OR LOGON