



SP3 PREMIUM SURGE PROTECTOR 2.0

ELECTRICAL	
Rated Voltage	110-250V a.c.
Rated Current	0.05A
Frequency	50Hz / 60Hz
Led	Power Dissipation: 100mWatt, Forward Current: 25Amp
Maximum Spike Voltage	6,000V
Maximum Spike Current	21,000A
L-N	7,000A
L-E	7,000A
N-E	7,000A
Maximum Energy Dissipation	660J
L-N	220J
L-E	220J
N-E	220J
Response Time	<1 ns
EMI/RFI Noise Filtration	150KHz to 100MHz, up to 43dB reduction
L-E	220J
N-E	220J
ENVIRONMENTAL	
Ambient Operating Temperature	0°C - 50°C / 32°F - 122°F (For indoor use only)
Degree Of Protection	Ordinary
MATERIAL	
Material (Enclosure)	Polycarbonate
Rim	Aluminium
SIZE AND WEIGHT	
Dimension (Diameter x Depth)	Ø67.3 x 51.5mm
Weight	Estimated 90gm
Function	Protect appliances against power disturbances such as voltage surge or spikes. Grounding status indicator. Complete 3-line protection (Live-Neutral, Neutral-Earth, Live-Earth)



www.eubiq.com

EUBIQ PRIVATE LIMITED. 9 JOO KOON CRESCENT SINGAPORE 629025
ALL RIGHTS RESERVED. EUBIQ AND GSS ARE REGISTERED TRADEMARKS OF EUBIQ PTE LTD.

DISCLAIMER: EUBIQ PRIVATE LIMITED RESERVES THE RIGHT TO ALTER ANY DETAILS OF SPECIFICATIONS OR EQUIPMENT WITHOUT PRIOR NOTICE. DETAILS OF SPECIFICATIONS AND EQUIPMENT ARE ALSO SUBJECT TO CHANGES TO SUIT LOCAL STANDARDS, CONDITIONS AND REQUIREMENTS. PLEASE CONSULT YOUR LOCAL DEALER FOR MORE INFORMATION OR LOGON TO EUBIQ WEBSITE.